Contact terminal A


KT-279 102 300

Item KT-279102300

GO TO PRODUCT

Partner for Future Technology

INGUN SELECTION








1:1





General data

Product group:	Contact terminals (KT)
Series:	KT-279
Sub-series:	KT-279
Grid:	3.5 mm [137 mil]
Type of contact terminal connection:	Solder connection
Magnetic:	Yes
Installation type:	Press-in
Quick-exchange system:	No
Surface area:	A gold
Material:	1 brass
Knurl:	No
RoHS-compliant:	RoHS-3;6c

Mounting hole

Mounting hole in CEM1:	0.98 - 0.99 mm [.038 - .038 in]
Mounting hole in FR4:	0.98 - 0.99 mm [.038 - .038 in]

Mechanical data

Collar height:	01
Total length:	4 mm [.157 in]
Shaft diameter:	1 mm [.039 in]
Latching lug:	No

Tip style data

Tip style:	02 flat
Tip diameter:	3 mm [.118 in]

INGUN Prüfmittelbau GmbH
Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com

Learn more about
Test probes

Prices and delivery times on request.
Technical changes reserved. 02/25_GB

ingun.com

CONTACT TERMINALS