Coaxial cable, pre-wired


SE-RG316-50MCXMG150

Item SE-RG316-0014

GO TO PRODUCT


ingun®
Partner for Future Technology

- Plug or cable assemblies for RF test probes (HFS)



1:1





General data

Product group:	Assemblies
Series:	SE-RG316
Sub-series:	SE-RG316 plug
Min. temperature:	- 55 °C [- 131 °F]
Max. temperature:	+ 155 °C [+ 311 °F]
RoHS-compliant:	RoHS-3

Cable data

Cable length:	150 cm [59.0 in]
Cable type:	RG_316_/U
Kink protection cable:	Shrink-on sleeve, black, 20 mm
Attenuation Fmax:	2.44 dB

Connector data

Interface 1:	MCX
Interface gender 1:	M signal conductor male / plug
Version 1:	Straight
Interface 2:	Open cable end

Electrical data

Maximum frequency:	3 GHz
Impedance:	50 Ohm
Cable shielding:	Simple
Maximum performance:	78 W
Performance coefficient:	135 RG316
Dielectric strength:	0.75 kV
Attenuation coefficient a:	0,77270 RG316 nominal
Attenuation coefficient b:	0,09720 RG316 nominal

INGUN Prüfmittelbau GmbH
Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com

Learn more about
Test probes

PLUG AND CABLE

Prices and delivery times on request.
Technical changes reserved. 02/25_GB

ingun.com